



DDR4 2666MHz / 2400MHz Long DIMM

Module spec:	288-pin DIMM (For desktop PCs)
Frequency Speed:	2666MHz (PC3-21300) 2400MHz (PC3-19200)
Voltage:	1.2V
Operating temperature:	0° – 85° C
System Compatibility:	Windows® Vista™ / Windows® 7 / 8 / 10, mac OS X : 10.X and later

Available capacities: 4GB, 8GB and 16GB



DDR4 2666MHz / 2400 MHz Short DIMM

Module spec:	260-pin SO-DIMM (For notebooks and mini PCs)
Frequency Speed:	2666MHz (PC3-21300) 2400MHz (PC3-19200)
Voltage:	1.2V
Operating temperature:	0° – 85° C
System Compatibility:	Windows® Vista™ / Windows® 7 / 8 / 10, mac OS X : 10.X and later

Available capacities: 4GB, 8GB and 16GB



2.5 SSD MS11 MS12 MS13

Interface:	SATA 6Gb/s
Performance(Max.):	Read speed up to 550MB/s Write speed up to 500MB/s
Dimensions:	100mmL x 70mmW x 7mmH
Operating temperature:	0° C – 70° C
Storage temperature:	-40° C – 85° C

Available capacities: 120GB, 240GB and 480GB

Micro SD A1

- Available capacities: 32GB, 64GB, 128GB and 256GB
- Performance:
- 256GB: Transfer speeds up to 100MB/s, write speeds up to 75MB/s
 - 64-128GB: Transfer speeds up to 95MB/s, write speeds up to 45MB/s
 - 32GB: Transfer speeds up to 95MB/s, write speeds up to 25MB/s
- Dimensions: 15mmL x 11mmW x 1mmH
- Operating temperature: -25°C – 85°C
- Storage temperature: -40°C – 85°C



MT60 USB 3.1

- Interface: USB 3.1 (backward compatible with USB 2.0) and microUSB
- Performance: Transfer speeds up to 210MB/s, write speeds up to 50MB/s
- Dimensions: 28mmL x 15mmW x 7mmH
- Operating temperature: 0°C – 70°C
- Storage temperature: -25°C – 85°C
- Available capacities: 16GB, 32GB and 64GB



USB 3.1 MU39

- Interface: USB 3.1 Gen 1 (USB 3.0, USB 2.0 compatible)
- Performance: Transfer speeds up to 130MB/s, write speeds lower
- Dimensions: 52mmL x 19mmW x 7.8mmH
- Operating temperature: 0° – 60° C
- Storage temperature: -25° – 85° C
- Available capacities: 16GB, 32GB, 64GB, 128GB and 256GB

